

Safety Data Sheet

according to UK REACH Regulation

FuturAcryl 2000 Flüssigkeit

Revision date: 11.03.2025

Product code: 650561

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

FuturAcryl 2000 Flüssigkeit

Further trade names

Art.-Nr.: 650561, 650562

UFI:

7J10-907R-500V-RTDX

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Denture base material

1.3. Details of the supplier of the safety data sheet

Company name:	Schütz Dental GmbH	
Street:	Dieselstrasse 5-6	
Place:	D-61191 Rosbach (Germany)	
Telephone:	+49 (0) 6003 814-0	Telefax: +49 (0) 6003 814-906
E-mail:	info@schuetz-dental.de	
Contact person:	Dr. Uwe Krichbaum	Telephone: +49 (0) 6003 814-650
Internet:	www.schuetz-dental.de	
Responsible Department:	Technische Dokumentation	

1.4. Emergency telephone number:

+49 (0) 6003 814-0 Schütz Dental (8:00 - 17:00 Uhr) or +49 (0) 6131 19240 University Mainz (24 h)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 2; H225
 Skin Irrit. 2; H315
 Skin Sens. 1; H317
 STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

methyl methacrylate
 tetramethylene dimethacrylate

Signal word: Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
------	---

Safety Data Sheet

according to UK REACH Regulation

FuturAcryl 2000 Flüssigkeit

Revision date: 11.03.2025

Product code: 650561

Page 2 of 10

P241	smoking.
P261	Use explosion-proof electrical/ventilating/lighting equipment.
P303+P361+P353	Avoid breathing dust/fume/gas/mist/vapours/spray.
P405	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P501	Store locked up.
	Dispose of waste according to applicable legislation.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:



Hazard statements

H317

Precautionary statements

P261-P501

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
80-62-6	methyl methacrylate			75 - < 100 %
	201-297-1	607-035-00-6		
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			
2082-81-7	tetramethylene dimethacrylate			2.5 - < 10 %
	218-218-1	607-134-00-4		
	Skin Sens. 1B; H317			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
80-62-6	201-297-1	methyl methacrylate	75 - < 100 %
	oral: LD50 = 7.872 mg/kg mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an

Safety Data Sheet

according to UK REACH Regulation

FuturAcryl 2000 Flüssigkeit

Revision date: 11.03.2025

Product code: 650561

Page 3 of 10

ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet
Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.
Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Safety Data Sheet

according to UK REACH Regulation

FuturAcryl 2000 Flüssigkeit

Revision date: 11.03.2025

Product code: 650561

Page 4 of 10

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Recommended storage temperature 10 - 25 °C

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Denture base material

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Tested protective gloves must be worn

Suitable material:

Butyl caoutchouc (butyl rubber)

NBR (Nitrile rubber)

Permeation time (maximum wear duration): 0,3 mm: 60 min.

Permeation time (maximum wear duration): 0,11 mm: 10 min.

Skin protection

Protective clothing.

Respiratory protection

Usually no personal respiratory protection necessary.

Respiratory protection necessary at: high concentrations

Filter type: A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Liquid

Colour:

colourless

Melting point/freezing point:

not determined

Safety Data Sheet

according to UK REACH Regulation

FuturAcryl 2000 Flüssigkeit

Revision date: 11.03.2025

Product code: 650561

Page 5 of 10

Boiling point or initial boiling point and boiling range:	101 °C
Flammability:	not determined
Lower explosion limits:	2,1 vol. %
Upper explosion limits:	12,5 vol. %
Flash point:	10 °C
Auto-ignition temperature:	430 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	No
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	47 hPa
Density (at 20 °C):	0,94 g/cm ³
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Hazardous polymerisation:

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to UK REACH Regulation

FuturAcryl 2000 Flüssigkeit

Revision date: 11.03.2025

Product code: 650561

Page 6 of 10

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
80-62-6	methyl methacrylate				
	oral	LD50 7.872 mg/kg mg/kg			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (methyl methacrylate; tetramethylene dimethacrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (methyl methacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Other information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

The product is not: Ecotoxic.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Safety Data Sheet

according to UK REACH Regulation

FuturAcryl 2000 Flüssigkeit

Revision date: 11.03.2025

Product code: 650561

Page 7 of 10

Disposal recommendations

Do not allow to enter into surface water or drains. Send to a hazardous waste incinerator facility under observation of official regulations.

List of Wastes Code - residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1247
14.2. UN proper shipping name: 1247 METHYLMETHACRYLAT, MONOMER, STABILISIERT, Gemisch
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Limited quantity: 1L
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Other applicable information (land transport)

E2

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1247
14.2. UN proper shipping name: 1247 METHYLMETHACRYLAT, MONOMER, STABILISIERT, Gemisch
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Limited quantity: 1L

Other applicable information (inland waterways transport)

E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED mixture
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Safety Data Sheet

according to UK REACH Regulation

FuturAcryl 2000 Flüssigkeit

Revision date: 11.03.2025

Product code: 650561

Page 8 of 10

Marine pollutant: Nein
EmS: F-E,S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED mixture
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1.

Safety Data Sheet

according to UK REACH Regulation

FuturAcryl 2000 Flüssigkeit

Revision date: 11.03.2025

Product code: 650561

Page 9 of 10

Abbreviations and acronyms

Flam. Liq: Flammable liquids
 Skin Irrit: Skin irritation
 Skin Sens: Skin sensitisation
 STOT SE: Specific target organ toxicity - single exposure
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 EC/EEC: European Community/European Economic Community
 EU: European Union
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 M-factor: Multiplying factor
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 IATA: International Air Transport Association
 DGR: Dangerous Goods Regulations
 ICAO: International Civil Aviation Organization
 TI: Technical Instructions
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
 assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.

Safety Data Sheet

according to UK REACH Regulation

FuturAcryl 2000 Flüssigkeit

Revision date: 11.03.2025

Product code: 650561

Page 10 of 10

H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)