Safety Data Sheet

according to UK REACH Regulation

Sebond Smart

Revision date: 12.08.2024 Product code: 640066 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sebond Smart

Further trade names Art.-Nr.: 640066

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Dental Bonding

1.3. Details of the supplier of the safety data sheet

Company name: Schütz Dental GmbH Street: Dieselstrasse 5-6

Place: D-61191 Rosbach (Germany)

Telephone: +49 (0) 6003 814-0 Telefax: +49 (0) 6003 814-906

E-mail: info@schuetz-dental.de

Contact person: Dr. Uwe Krichbaum Telephone: +49 (0) 6003 814-650

Internet: www.schuetz-dental.de
Responsible Department: Technische Dokumentation

1.4. Emergency telephone +49 (0) 6003 814-0 Schütz Dental (8:00 - 17:00 Uhr) or +49 (0) 6131 19240

number: University Mainz (24 h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

methyl methacrylate

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

according to UK REACH Regulation

Sebond Smart

Revision date: 12.08.2024 Product code: 640066 Page 2 of 10

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P405 Store locked up.

P501 Dispose of contents/container to Dispose of waste according to applicable legislation..

Special labelling of certain mixtures

EUH018 In use may form flammable/explosive vapour-air mixture.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:





Hazard statements

H317

Precautionary statements

P261-P501

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

| CAS No | Chemical name | | | Quantity |
|---------|---|--------------|----------|--------------|
| | EC No Index No REACH No | | REACH No | |
| | Classification (GB CLP Regulation) | | | |
| 80-62-6 | methyl methacrylate | | | 75 - < 100 % |
| | 201-297-1 | 607-035-00-6 | | |
| | Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| OAO NI- | FONE | Ohami'adaa aa | 0 |
|---------|------------------|--|--------------|
| CAS No | EC No | Chemical name | Quantity |
| | Specific Conc. I | Specific Conc. Limits, M-factors and ATE | |
| 80-62-6 | 201-297-1 | methyl methacrylate | 75 - < 100 % |
| | oral: LD50 = 7. | oral: LD50 = 7.872 mg/kg mg/kg | |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing and wash it before reuse.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

Safety Data Sheet

according to UK REACH Regulation

Sebond Smart

Revision date: 12.08.2024 Product code: 640066 Page 3 of 10

After ingestion

Rinse mouth immediately and drink 1 glass of of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet

Foam

Carbon dioxide (CO2)

Extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately.

according to UK REACH Regulation

Sebond Smart

Revision date: 12.08.2024 Product code: 640066 Page 4 of 10

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Recommended storage temperature 10 - 25 °C

Hints on joint storage

No special measures are necessary.

7.3. Specific end use(s)

Dental Bonding

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m³ | fibres/ml | Category | Origin |
|---------|---------------------|-----|-------|-----------|---------------|--------|
| 80-62-6 | Methyl methacrylate | 50 | 208 | | TWA (8 h) | WEL |
| | | 100 | 416 | | STEL (15 min) | WEL |

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection.

Hand protection

Tested protective gloves must be worn

Butyl caoutchouc (butyl rubber)

NBR (Nitrile rubber)

Permeation time (maximum wear duration): 0,3 mm: 60 min. Permeation time (maximum wear duration): 0,11 mm: 10 min.

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: colourless

Melting point/freezing point: - 48 °C
Boiling point or initial boiling point and 101 °C

boiling range:

Flammability: not determined Lower explosion limits: 2,1

according to UK REACH Regulation

| | | Sebond Smart | |
|---------|--------------------|----------------------|--------------|
| Revisio | n date: 12.08.2024 | Product code: 640066 | Page 5 of 10 |

Upper explosion limits: 12,5
Flash point: 10 °C
Auto-ignition temperature: 430 °C
Decomposition temperature: not determined
pH-Value: not determined
Viscosity / kinematic: not determined
Water solubility: 1,6 g/l

Solubility in other solvents not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 47 hPa

(at 20 °C)

Density: 0,94 g/cm³
Relative vapour density: not determined
Particle characteristics: not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive. In use, may form flammable/explosive vapour-air mixture.

Oxidizing properties

The product is not: oxidising.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Hazardous polymerisation:

10.4. Conditions to avoid

none

10.5. Incompatible materials

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to UK REACH Regulation

Sebond SmartRevision date: 12.08.2024Product code: 640066Page 6 of 10

| CAS No | Chemical name | | | | |
|---------|---------------------|---------------------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 80-62-6 | methyl methacrylate | | | | |
| | 1 - 1 - 11 | LD50 7.872 mg/kg mg/kg | | | |

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (methyl methacrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (methyl methacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Other information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Safety Data Sheet

according to UK REACH Regulation

Sebond Smart

Revision date: 12.08.2024 Product code: 640066 Page 7 of 10

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1247

14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 386 676
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 339
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1247

14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 386 676
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1247

14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: 386
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-D
Segregation group: 3 - bromates

Air transport (ICAO-TI/IATA-DGR)

according to UK REACH Regulation

Sebond Smart

Revision date: 12.08.2024 Product code: 640066 Page 8 of 10

14.1. UN number or ID number: UN 1247

14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: A209
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

Hazchem code: 3YE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to Directive

2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1.

according to UK REACH Regulation

Sebond Smart

Revision date: 12.08.2024 Product code: 640066 Page 9 of 10

Abbreviations and acronyms

Flam. Liq: Flammable liquids Skin Irrit: Skin irritation Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

EC/EEC: European Community/European Economic Community

EU: European Union

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

M-factor: Multiplying factor

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to GB CLP Regulation

| Classification | Classification procedure |
|---------------------|--------------------------|
| Flam. Liq. 2; H225 | |
| Skin Irrit. 2; H315 | Calculation method |
| Skin Sens. 1; H317 | Calculation method |
| STOT SE 3; H335 | Calculation method |

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

EUH018 In use may form flammable/explosive vapour-air mixture.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Safety Data Sheet

according to UK REACH Regulation

Sebond Smart

Revision date: 12.08.2024 Product code: 640066 Page 10 of 10

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)