

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FuturaPress LT Com4 Flüssigkeit

Revision date: 15.04.2024

Product code: 750161,750162

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

FuturaPress LT Com4 Flüssigkeit

Product group: liquid component
 UFI: 3SJ0-D5EN-620H-6P2A

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Manufacture of dental products.

1.3. Details of the supplier of the safety data sheet

Company name: Schütz Dental GmbH
 Street: Dieselstrasse 5-6
 Place: D-61191 Rosbach v.d.H
 Telephone: +49 (0) 6003 - 814-0
 E-mail: info@schuetz-dental.de
 Internet: www.schuetz-dental.de
 Responsible Department: +49 (0) 6003 - 814-630
 Telefax: +49 (0) 6003 - 814-906

1.4. Emergency telephone

number: +49 (0) 6131 - 19240
 Poison Information Centre, University Mainz (24 h)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225
 Skin Irrit. 2; H315
 Skin Sens. 1; H317
 STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Methyl methacrylate
 1,4-Butandiol dimethacrylate

Signal word: Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FuturaPress LT Com4 Flüssigkeit

Revision date: 15.04.2024

Product code: 750161,750162

Page 2 of 10

P302+P352	protection.
P321	IF ON SKIN: Wash with plenty of Water and soap.
P333+P313	Specific treatment (see ... on this label).
P362+P364	If skin irritation or rash occurs: Get medical advice/attention.
P370+P378	Take off contaminated clothing and wash it before reuse.
P403+P235	In case of fire: Use Foam, Extinguishing powder, Carbon dioxide (CO ₂) to extinguish.
P501	Store in a well-ventilated place. Keep cool.
	Dispose of contents/container to as hazardous waste – in accordance with local and national legislation – suitable, approved incineration plant for combustible, organic-chemical waste.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

mixture based on methyl methacrylate

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
80-62-6	Methyl methacrylate			90 - < 95 %
	201-297-1		01-2119452498-28	
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			
2082-81-7	1,4-Butandiol dimethacrylate			5 - < 10 %
	218-218-1		01-2119967415-30	
	Skin Sens. 1; H317			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
80-62-6	201-297-1	Methyl methacrylate	90 - < 95 %
		inhalation: LC50 = 29,8 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
2082-81-7	218-218-1	1,4-Butandiol dimethacrylate	5 - < 10 %
		dermal: LD50 = > 3000 mg/kg; oral: LD50 = > 10000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FuturaPress LT Com4 Flüssigkeit

Revision date: 15.04.2024

Product code: 750161,750162

Page 3 of 10

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Do NOT induce vomiting. Rinse mouth. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause respiratory irritation. May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour. Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Schutzhandschuhe und Augen- / Gesichtsschutz tragen. Einatmen von Dampf vermeiden. Siehe Abschnitt: 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

When using do not eat, drink, smoke, sniff. Use only in well-ventilated areas. Do not breathe gas/fumes/vapour/spray.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FuturaPress LT Com4 Flüssigkeit

Revision date: 15.04.2024

Product code: 750161,750162

Page 4 of 10

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Caution! Transport usually takes place at temperatures above the flash point.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.
Protect from direct sunlight.

Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising, Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
80-62-6	Methyl methacrylate	50	-		TWA (8 h)	
		100	-		STEL (15 min)	

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
80-62-6	Methyl methacrylate			
Worker DNEL, long-term		inhalation		208 mg/m ³
Worker DNEL, long-term		dermal		17 mg/kg bw/day

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Wear suitable protective gloves. For protection against splashes: Butyl; EN 374. For protection against immersion: Butyl; 0.7 mm or thicker, EN 374. The suitability of gloves should be agreed with the manufacturer. In case of contamination or if the breakthrough time is exceeded, change gloves. Resistance of the glove material: see information from the glove manufacturer.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FuturaPress LT Com4 Flüssigkeit

Revision date: 15.04.2024

Product code: 750161,750162

Page 5 of 10

Respiratory protection

Wear suitable respiratory protection if engineering controls are inadequate or non-existent and exposure is expected to exceed the DNEL (derived exposure level below which the substance does not cause adverse effects on human health). A suitable respiratory mask with filter type A (EN141 or EN405) is recommended. If particularly high vapour concentrations are formed, a self-contained breathing apparatus may be necessary.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic
Melting point/freezing point:	-48 °C
Boiling point or initial boiling point and boiling range:	100,5 °C
Flammability:	not applicable not applicable
Lower explosion limits:	2,1 vol. %
Upper explosion limits:	12,5 vol. %
Flash point:	10 °C
Auto-ignition temperature:	421 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility: (at 20 °C)	12,5 g/L
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	1,38
Vapour pressure: (at 20 °C)	36 hPa
Density (at 15,5 °C):	0,949 g/cm ³
Relative vapour density: (at 20 °C)	3,5

9.2. Other information**Information with regard to physical hazard classes**

Self-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Oxidizing properties	
Not oxidising.	

Other safety characteristics

Evaporation rate:	not determined
Solid content:	not determined
Viscosity / dynamic: (at 20 °C)	0,53 mPa·s

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable, Vapours can form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FuturaPress LT Com4 Flüssigkeit

Revision date: 15.04.2024

Product code: 750161,750162

Page 6 of 10

10.3. Possibility of hazardous reactions

Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators. Protect from direct sunlight.

10.5. Incompatible materials

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix tested

	Dose	Species	Source
LD50, oral	7870 mg/kg	Rat	
LD50, dermal	> 5000 mg/kg	Rabbit	
LC50, inhalation (vapour) (4 h)	78 mg/l	Rat	

ATEmix calculated

ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
80-62-6	Methyl methacrylate				
	oral	LD50 >5000 mg/kg	Rat	OECD 401	
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation vapour	LC50 29,8 mg/l	Rat		
2082-81-7	1,4-Butandiol dimethacrylate				
	oral	LD50 > 10000 mg/kg	Rat		
	dermal	LD50 > 3000 mg/kg	Rabbit		

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Methyl methacrylate; 1,4-Butandiol dimethacrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Methyl methacrylate)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FuturaPress LT Com4 Flüssigkeit

Revision date: 15.04.2024

Product code: 750161,750162

Page 7 of 10

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Acute (short-term) fish toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
80-62-6	Methyl methacrylate					
	Acute fish toxicity	LC50 > 79 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203	
	Acute algae toxicity	ErC50 > 110 mg/l	72 h	Selenastrum capricornutum	OECD 201	
	Acute crustacea toxicity	EC50 69 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202	
	Crustacea toxicity	NOEC 37 mg/l	21 d	Daphnia magna (Big water flea)	OECD 202	
2082-81-7	1,4-Butandiol dimethacrylate					
	Acute fish toxicity	LC50 32,5 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute crustacea toxicity	EC50 7,51 mg/l	48 h	Daphnia magna (Big water flea)	OECD 211	
	Crustacea toxicity	NOEC 7,51 mg/l		Selenastrum capricornutum		

12.2. Persistence and degradability

Biodegradable.

12.3. Bioaccumulative potential

On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment is unlikely.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	Methyl methacrylate	1,38
2082-81-7	1,4-Butandiol dimethacrylate	3,1

12.4. Mobility in soil

Mobility in soil: No adsorption in soil or sediment.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FuturaPress LT Com4 Flüssigkeit

Revision date: 15.04.2024

Product code: 750161,750162

Page 8 of 10

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1247
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	339
Tunnel restriction code:	D/E

Other applicable information (land transport)

SAPT: > 60 °C

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1247
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L
Excepted quantity:	E2

Other applicable information (inland waterways transport)

SAPT: > 60 °C

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1247
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-D

Other applicable information (marine transport)

SAPT: > 60 °C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1247
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es):	3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FuturaPress LT Com4 Flüssigkeit

Revision date: 15.04.2024

Product code: 750161,750162

Page 9 of 10

14.4. Packing group:	II	
Hazard label:	3	
Limited quantity Passenger:	1 L	
Passenger LQ:	Y-341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		353
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		364
IATA-max. quantity - Cargo:		60 L

Other applicable information (air transport)

SAPT: > 60 °C

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquids.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Directive 2010/75/EU on industrial emissions: 90 % (854,1 g/l)

Directive 2004/42/EC on VOC in paints and varnishes: 90 % (854,1 g/l)

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

FuturaPress LT Com4 Flüssigkeit

Revision date: 15.04.2024

Product code: 750161,750162

Page 10 of 10

Abbreviations and acronyms

Flam. Liq: Flammable liquid

Skin Irrit: Skin irritation

Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)