

## Safety Data Sheet

## Relight Versiegelungslack

Revision: 19.11.2025

Product code: 689121-1

Page 1 of 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Relight Versiegelungslack

**Further trade names**

Art.-Nr. 689121

UFI:

A018-71MW-0F6S-9VYK

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Dental Lack / dental lacquer

**1.3. Details of the supplier of the safety data sheet**

Company name:	Schütz Dental GmbH	
Street:	Dieselstrasse 5-6	
Place:	D-61191 Rosbach (Germany)	
Telephone:	+49 (0) 6003 814-0	Telefax: +49 (0) 6003 814-906
E-mail:	info@schuetz-dental.de	
Contact person:	Dr. Uwe Krichbaum	Telephone: +49 (0) 6003 814-650
Internet:	www.schuetz-dental.de	
Responsible Department:	Technische Dokumentation	

**1.4. Emergency telephone number:**

+49 (0) 6003 814-0 Schütz Dental (8:00 - 17:00 Uhr) or +49 (0) 6131 19240 University Mainz (24 h)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225  
 Skin Irrit. 2; H315  
 Eye Irrit. 2; H319  
 Skin Sens. 1; H317  
 STOT SE 3; H335  
 Aquatic Chronic 4; H413

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Hazard components for labelling**

methyl methacrylate  
 2-Propenoic acid, reaction product with dipentaerythritole

**Signal word:** Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

## Safety Data Sheet

## Relight Versiegelungslack

Revision: 19.11.2025

Product code: 689121-1

Page 2 of 10

H413 May cause long lasting harmful effects to aquatic life.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of waste according to applicable legislation.

**Labelling of packages where the contents do not exceed 125 ml****Signal word:** Danger**Pictograms:****Hazard statements**

H317-H413

**Precautionary statements**

P501

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
80-62-6	methyl methacrylate			50 - < 75 %
	201-297-1	607-035-00-6		
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			
56744-60-6	Bisphenole-A-ethoxylate(4) dimethacrylate			10 - < 25 %
	260-363-8	607-134-00-4		
	Aquatic Chronic 4; H413			
1384855-91-7	2-Propenoic acid, reaction product with dipentaerythritole			10 - < 25 %
	Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H319 H317 H412			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
80-62-6	201-297-1	methyl methacrylate	50 - < 75 %
	oral: LD50 = 7.872 mg/kg mg/kg		

**SECTION 4: First aid measures****4.1. Description of first aid measures**

# Safety Data Sheet

## Relight Versiegelungslack

Revision: 19.11.2025

Product code: 689121-1

Page 3 of 10

### General information

Remove/Take off immediately all contaminated clothing.

### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

### After contact with skin

In case of skin irritation, consult a physician.

### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

### After ingestion

Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder. Water mist

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

No special measures are necessary.

### 5.3. Advice for firefighters

No special measures are necessary.

### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Provide adequate ventilation.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

#### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

## Safety Data Sheet

## Relight Versiegelungslack

Revision: 19.11.2025

Product code: 689121-1

Page 4 of 10

**Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Avoid: generation/formation of aerosols

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

**Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Protect against: Light

Recommended storage temperature 10 - 25 °C

**7.3. Specific end use(s)**

Dental Lack / dental lacquer

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

**8.2. Exposure controls****Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear eye/face protection.

**Hand protection**

Tested protective gloves must be worn

Suitable material:

Butyl caoutchouc (butyl rubber)

NBR (Nitrile rubber)

Permeation time (maximum wear duration): 0,3 mm: 60 min

Permeation time (maximum wear duration): 0,11 mm: 10 min

**Skin protection**

Use of protective clothing

**Respiratory protection**

Usually no personal respiratory protection necessary.

In case of inadequate ventilation wear respiratory protection.

Filter type: A

## Safety Data Sheet

## Relight Versiegelungslack

Revision: 19.11.2025

Product code: 689121-1

Page 5 of 10

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Melting point/freezing point:	- 48 °C °C
Boiling point or initial boiling point and boiling range:	101 °C
Flammability:	not determined
Lower explosion limits:	2,1 vol. %
Upper explosion limits:	12,5 vol. %
Flash point:	10 °C
Auto-ignition temperature:	430 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	No
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	47 hPa
Density:	not determined
Relative vapour density:	not determined
Particle characteristics:	not applicable

**9.2. Other information****Information with regard to physical hazard classes**

Explosive properties

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No special measures are necessary.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Hazardous polymerisation:

**10.4. Conditions to avoid**

No special measures are necessary.

**10.5. Incompatible materials**

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.

**SECTION 11: Toxicological information****11.1. Information on hazard classes**

## Safety Data Sheet

## Relight Versiegelungslack

Revision: 19.11.2025

Product code: 689121-1

Page 6 of 10

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
80-62-6	methyl methacrylate				
	oral	LD50 7.872 mg/kg mg/kg			

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

**Sensitising effects**

May cause an allergic skin reaction. (methyl methacrylate; 2-Propenoic acid, reaction product with dipentaerythritole)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (methyl methacrylate)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards****Other information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**SECTION 12: Ecological information****12.1. Toxicity**

May cause long lasting harmful effects to aquatic life.

Harmful to aquatic life with long lasting effects.

**12.2. Persistence and degradability**

The product has not been tested.

**12.3. Bioaccumulative potential**

The product has not been tested.

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

## Safety Data Sheet

## Relight Versiegelungslack

Revision: 19.11.2025

Product code: 689121-1

Page 7 of 10

## Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

## Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

## List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

## Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

## Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1247  
**14.2. UN proper shipping name:** 1247 METHYLMETHACRYLAT, MONOMER, STABILISIERT, Gemisch  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 1L  
 Transport category: 2  
 Hazard No: 339  
 Tunnel restriction code: D/E

## Other applicable information (land transport)

E2

## Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1247  
**14.2. UN proper shipping name:** 1247 METHYLMETHACRYLAT, MONOMER, STABILISIERT, Gemisch  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 1L

## Other applicable information (inland waterways transport)

E2

## Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1247  
**14.2. UN proper shipping name:** METHYL METHACRYLATE MONOMER, STABILIZED mixture  
**14.3. Transport hazard class(es):** 3

## Safety Data Sheet

## Relight Versiegelungslack

Revision: 19.11.2025

Product code: 689121-1

Page 8 of 10

**14.4. Packing group:**

II

Hazard label:

3



Marine pollutant:

Nein

EmS:

F-E,S-D

**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number or ID number:**

UN 1247

**14.2. UN proper shipping name:**

METHYL METHACRYLATE MONOMER, STABILIZED mixture

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

II

Hazard label:

3

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:

No

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive  
2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,2.

**Safety Data Sheet****Relight Versiegelungslack**

Revision: 19.11.2025

Product code: 689121-1

Page 9 of 10

**Abbreviations and acronyms**

Flam. Liq. 2: Flammable liquids, hazard category 2  
Skin Irrit. 2: Skin irritation, hazard category 2  
Eye Irrit. 2: Eye irritation, hazard category 2  
Skin Sens. 1: Skin sensitisation, hazard category 1  
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3  
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3  
Aquatic Chronic 4: Hazardous to the aquatic environment, long-term hazard category: Chronic 4  
CLP: Classification, labelling and Packaging  
REACH: Registration, Evaluation and Authorization of Chemicals  
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
UN: United Nations  
EC/EEC: European Community/European Economic Community  
EU: European Union  
CAS: Chemical Abstracts Service  
DNEL: Derived No Effect Level  
DMEL: Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration  
ATE: Acute toxicity estimate  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%  
LL50: Lethal loading, 50%  
EL50: Effect loading, 50%  
EC50: Effective Concentration 50%  
ErC50: Effective Concentration 50%, growth rate  
NOEC: No Observed Effect Concentration  
BCF: Bio-concentration factor  
PBT: persistent, bioaccumulative, toxic  
vPvB: very persistent, very bioaccumulative  
M-factor: Multiplying factor  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Regulations concerning the international carriage of dangerous goods by rail  
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)  
IMDG: International Maritime Code for Dangerous Goods  
EmS: Emergency Schedules  
MFAG: Medical First Aid Guide  
IATA: International Air Transport Association  
DGR: Dangerous Goods Regulations  
ICAO: International Civil Aviation Organization  
TI: Technical Instructions  
MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
IBC: Intermediate Bulk Container  
SVHC: Substance of Very High Concern  
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

## Safety Data Sheet

## Relight Versiegelungslack

Revision: 19.11.2025

Product code: 689121-1

Page 10 of 10

**Classification for mixtures and used evaluation method**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Chronic 4; H413	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*