

Safety Data Sheet

Sebond Grip

Revision: 18.11.2025

Product code: 644092-1

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Sebond Grip

Further trade names

Art.-Nr. 644092

UFI:

E379-XHRW-UTJT-EM55

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Abdeckmittel / covering material

1.3. Details of the supplier of the safety data sheet

Company name: Schütz Dental GmbH

Street: Dieselstrasse 5-6

Place: D-61191 Rosbach (Germany)

Telephone: +49 (0) 6003 814-0

Telefax: +49 (0) 6003 814-906

E-mail: info@schuetz-dental.de

Contact person: Dr. Uwe Krichbaum

Telephone: +49 (0) 6003 814-650

Internet: www.schuetz-dental.de

Responsible Department: Technische Dokumentation

1.4. Emergency telephone

+49 (0) 6003 814-0 Schütz Dental (8:00 - 17:00 Uhr) or +49 (0) 6131 19240

number:

University Mainz (24 h)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Skin Sens. 1; H317


Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

di-urethane dimethacrylate

2-[[[(butylamino)carbonyl]oxy]ethyl acrylate

Signal word: Warning**Pictograms:****Hazard statements**

H317

May cause an allergic skin reaction.

H411

Toxic to aquatic life with long lasting effects.

Precautionary statements

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

P280

Wear protective gloves.

P304+P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312

Call a POISON CENTER/doctor if you feel unwell.

P501

Dispose of waste according to applicable legislation.

Safety Data Sheet

Sebond Grip

Revision: 18.11.2025

Product code: 644092-1


Page 2 of 9

Labelling of packages where the contents do not exceed 125 ml

Signal word:

Warning

Pictograms:



Hazard statements

H317

Precautionary statements

P261-P280-P501

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
41137-60-4	di-urethane dimethacrylate			25 - < 50 %
	Skin Sens. 1B, Aquatic Chronic 2; H317 H411			
63225-53-6	2-[[[(butylamino)carbonyl]oxy]ethyl acrylate			2.5 - < 10 %
	Acute Tox. 4, Skin Sens. 1A, Aquatic Chronic 2; H332 H317 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
63225-53-6		2-[[[(butylamino)carbonyl]oxy]ethyl acrylate	2.5 - < 10 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists)	

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink 1 glass of water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Safety Data Sheet

Revision: 18.11.2025

Sebond Grip
Product code: 644092-1

Page 3 of 9

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.
Carbon dioxide
Extinguishing powder
Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

Use appropriate respiratory protection. In case of fire and/or explosion do not breathe fumes.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.
Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Local and general ventilation

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Always close containers tightly after the removal of product.
Protect against: Light
Recommended storage temperature 10 - 25 °C

Hints on joint storage

No special measures are necessary.

7.3. Specific end use(s)

Abdeckmittel / covering material

Safety Data Sheet

Sebond Grip

Revision: 18.11.2025

Product code: 644092-1

Page 4 of 9

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Additional advice on limit values**

To date, no national critical limit values exist.

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear eye/face protection.

Hand protection

Tested protective gloves must be worn

Suitable material:

Butyl caoutchouc (butyl rubber)

NBR (Nitrile rubber)

Permeation time (maximum wear duration): 0,3 mm: 60 min

Permeation time (maximum wear duration): 0,11 mm: 10 min

Skin protection

Use of protective clothing.

Respiratory protection

Usually no personal respiratory protection necessary.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:

Colour:

Melting point/freezing point:

not determined

Boiling point or initial boiling point and

251 °C

boiling range:

Flammability:

not determined

Lower explosion limits:

not determined

Upper explosion limits:

not determined

Flash point:

151 °C

Auto-ignition temperature:

>370 °C

Decomposition temperature:

not determined

pH-Value:

not determined

Viscosity / kinematic:

not applicable

Water solubility:

No

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

not determined

Vapour pressure:

not determined

Density:

not determined

Safety Data Sheet

Sebond Grip

Revision: 18.11.2025

Product code: 644092-1

Page 5 of 9

Relative vapour density:

not determined

Particle characteristics:

not determined

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Hazardous polymerisation:

10.4. Conditions to avoid

none

10.5. Incompatible materials

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
63225-53-6	2-[[[(butylamino)carbonyl]oxy]ethyl acrylate				
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (di-urethane dimethacrylate; 2-[[[(butylamino)carbonyl]oxy]ethyl acrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

Sebond Grip

Revision: 18.11.2025

Product code: 644092-1

Page 6 of 9

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Other information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080112 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish other than those mentioned in 08 01 11

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 3082

14.2. UN proper shipping name:ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Aliphatisches Urethandimethacrylat)**14.3. Transport hazard class(es):**

9

14.4. Packing group:

III

Safety Data Sheet

Sebond Grip

Revision: 18.11.2025

Product code: 644092-1

Page 7 of 9

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601 650

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

-

Inland waterways transport (ADN)**14.1. UN number or ID number:**

UN 3082

14.2. UN proper shipping name:ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Aliphatisches Urethandimethacrylat)**14.3. Transport hazard class(es):**

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601 650

Limited quantity:

5 L

Excepted quantity:

E1

Marine transport (IMDG)**14.1. UN number or ID number:**

UN 3082

14.2. UN proper shipping name:ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(di-urethane dimethacrylate)**14.3. Transport hazard class(es):**

9

14.4. Packing group:

III

Hazard label:

9



Special Provisions:

274 335 375 969

Limited quantity:

5 L

Excepted quantity:

E1

EmS:

F-A, S-F

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:**

UN 3082

14.2. UN proper shipping name:ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(di-urethane dimethacrylate)**14.3. Transport hazard class(es):**

9

14.4. Packing group:

III

Hazard label:

9



Special Provisions:

A97 A158 A197 A215

Limited quantity Passenger:

30 kg G

Safety Data Sheet

Sebond Grip

Revision: 18.11.2025

Product code: 644092-1

Page 8 of 9

Passenger LQ:	Y964	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:		964
IATA-max. quantity - Passenger:		450 L
IATA-packing instructions - Cargo:		964
IATA-max. quantity - Cargo:		450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: di-urethane dimethacrylate

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Information according to Directive 2012/18/EU (SEVESO III): E2 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	2 - obviously hazardous to water
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1.

Safety Data Sheet

Sebond Grip

Revision: 18.11.2025

Product code: 644092-1

Page 9 of 9

Abbreviations and acronyms

Acute Tox. 4: Acute toxicity, hazard category 4
 Skin Sens. 1: Skin sensitisation, hazard category 1
 Skin Sens. 1A: Skin sensitisation, hazard category 1A
 Skin Sens. 1B: Skin sensitisation, hazard category 1B
 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 EC/EEC: European Community/European Economic Community
 EU: European Union
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 M-factor: Multiplying factor
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H317 May cause an allergic skin reaction.
 H332 Harmful if inhaled.
 H411 Toxic to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)