

Safety Data Sheet

dialog Bonding Fluid

Revision: 19.11.2025

Product code: 643922

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

dialog Bonding Fluid

Further trade names

Art.-Nr.: 643922

UFI:

VP2H-E4AW-PRER-1G40

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Dental Bonding

1.3. Details of the supplier of the safety data sheet

Company name:	Schütz Dental GmbH	
Street:	Dieselstrasse 5-6	
Place:	D-61191 Rosbach (Germany)	
Telephone:	+49 (0) 6003 814-0	Telefax: +49 (0) 6003 814-906
E-mail:	info@schuetz-dental.de	
Contact person:	Dr. Uwe Krichbaum	Telephone: +49 (0) 6003 814-650
Internet:	www.schuetz-dental.de	
Responsible Department:	Technische Dokumentation	

1.4. Emergency telephone number:

+49 (0) 6003 814-0 Schütz Dental (8:00 - 17:00 Uhr) or +49 (0) 6131 19240 University Mainz (24 h)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225
 Skin Irrit. 2; H315
 Skin Sens. 1; H317
 STOT SE 3; H335
 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

methyl methacrylate
 di-urethane dimethacrylate

Signal word: Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet

dialog Bonding Fluid

Revision: 19.11.2025

Product code: 643922

Page 2 of 10

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P405 Store locked up.
- P501 Dispose of waste according to applicable legislation.

Labelling of packages where the contents do not exceed 125 ml**Signal word:** Danger**Pictograms:****Hazard statements**

H317

Precautionary statements

P261-P501

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
80-62-6	methyl methacrylate	50 - < 75 %
	201-297-1	607-035-00-6
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335	
41137-60-4	di-urethane dimethacrylate	25 - < 50 %
	Skin Sens. 1B, Aquatic Chronic 2; H317 H411	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
80-62-6	201-297-1	methyl methacrylate	50 - < 75 %
	oral: LD50 = 7.872 mg/kg mg/kg		

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

Safety Data Sheet

dialog Bonding Fluid

Revision: 19.11.2025

Product code: 643922

Page 3 of 10

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Local and general ventilation

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove/Take off immediately all contaminated clothing. Wash hands before breaks and after work. Do not get in eyes, on skin, or on clothing. Keep away from: Food and feedingstuffs

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

dialog Bonding Fluid

Revision: 19.11.2025

Product code: 643922

Page 4 of 10

Requirements for storage rooms and vessels

Put lids on containers immediately after use. Protect against: Light
Recommended storage temperature 10 - 25 °C

7.3. Specific end use(s)

Dental Bonding

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

8.2. Exposure controls**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear eye/face protection.

Hand protection

Tested protective gloves must be worn

Butyl caoutchouc (butyl rubber)

NBR (Nitrile rubber)

Permeation time (maximum wear duration): 0,3 mm: 60 min.

Permeation time (maximum wear duration): 0,11 mm: 10 min.

Respiratory protection

Usually no personal respirative protection necessary.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	clear
Melting point/freezing point:	- 48 °C
Boiling point or initial boiling point and boiling range:	101 °C
Flammability:	not determined
Lower explosion limits:	2,1 vol. %
Upper explosion limits:	12,5 vol. %
Flash point:	10 °C
Auto-ignition temperature:	430 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	No
Solubility in other solvents	not determined

Safety Data Sheet

dialog Bonding Fluid

Revision: 19.11.2025

Product code: 643922

Page 5 of 10

Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	47 hPa
Density:	not determined
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Hazardous polymerisation:

10.4. Conditions to avoid

No special measures are necessary.

10.5. Incompatible materials

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
80-62-6	methyl methacrylate				
	oral	LD50 7.872 mg/kg mg/kg			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (methyl methacrylate; di-urethane dimethacrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Safety Data Sheet**dialog Bonding Fluid**

Revision: 19.11.2025

Product code: 643922

Page 6 of 10

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (methyl methacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Other information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Send to a hazardous waste incinerator facility under observation of official regulations.

List of Wastes Code - residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

Safety Data Sheet

dialog Bonding Fluid

Revision: 19.11.2025

Product code: 643922

Page 7 of 10

14.1. UN number or ID number: UN 1247
14.2. UN proper shipping name: 1247 METHYLMETHACRYLAT, MONOMER, STABILISIERT
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Limited quantity: 1L
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Other applicable information (land transport)
 E2

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1247
14.2. UN proper shipping name: 1247 METHYLMETHACRYLAT, MONOMER, STABILISIERT
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Limited quantity: 1L

Other applicable information (inland waterways transport)
 E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Marine pollutant: Nein
 EmS: F-E,S-D
 Segregation group: 3 - bromates

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3

**14.5. Environmental hazards**

Safety Data Sheet

dialog Bonding Fluid

Revision: 19.11.2025

Product code: 643922

Page 8 of 10

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: di-urethane dimethacrylate

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): E2 Hazardous to the Aquatic Environment

Additional information: P5c

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,7,9,10,11,13,14.

Safety Data Sheet

dialog Bonding Fluid

Revision: 19.11.2025

Product code: 643922

Page 9 of 10

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
 Skin Irrit. 2: Skin irritation, hazard category 2
 Skin Sens. 1: Skin sensitisation, hazard category 1
 Skin Sens. 1B: Skin sensitisation, hazard category 1B
 STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
 CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 EC/EEC: European Community/European Economic Community
 EU: European Union
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 M-factor: Multiplying factor
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
 intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFAG: Medical First Aid Guide
 IATA: International Air Transport Association
 DGR: Dangerous Goods Regulations
 ICAO: International Civil Aviation Organization
 TI: Technical Instructions
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 SVHC: Substance of Very High Concern
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
 assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Chronic 2; H411	Calculation method

Safety Data Sheet**dialog Bonding Fluid**

Revision: 19.11.2025

Product code: 643922

Page 10 of 10

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)